

Vivitek D963HD



Produkt Highlights

- Helle 4500 ANSI Lumen mit hohem Kontrastwert 3000:1
- VividWheel III für verbesserte Farbdarstellung
- Anschlußoptionen u.a.: HDMI V1.3, RJ45, VGA-Out, USB
- 12V trigger für eine externe Verbindung von wireless Modulen
- 5W Lautsprecher

Produkt Fotos



Produkt Spezifikationen

Display Typ	DLP
Helligkeit	4500 ANSI Lumen
Native Auflösung	1080P (1920 x 1080)
Maximale Auflösung	WUXGA (1920 x 1200)
Kontrast Ratio	3,000:1
Lampenlebensdauer/Typ	2,000 /3,000 Std (Boost/Std. Mode), 300W
Throw Ratio	1.6 - 1.92:1
Bildgröße (Diagonale)	23.5" - 300"
Projektionsdistanz	1 - 10 m
Optik	F=2.5, f=23.5-28.2mm
Zoom Ratio	1.2x
Bilddarstellung	16:9 nativ, 4:3 kompatibel
Offset	130%
Keystone Korrektur	Auto Keystone, +/- 40°
Horizontale Frequenz	15, 30 - 90KHz
Vertikale Frequenz	43 - 85Hz
Lautsprecher	5W (Mono)
Lens Shift Range	N/A
Video Signale	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Anschlüsse	HDMI 1.3V (x2), VGA-In, S-Video, Component (YPbPr), Composite, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 12V Trigger, RS-232C, USB (Service)
Projektionen	Tisch- und Deckenmontage
Sicherheitsoptionen	Kensington® Security Slot, Security Bar, Keypad Lock
Maße (B x H x T)	332.8 x 254.6 x 113mm (13.1 "x 10" x 4.4")
Gewicht	3.4 Kg
Geräuschpegel	35dB/39dB (Std. / Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	370W (Boost Mode), 320W (Std. Mode), <1W (Standby Mode)
Standard Zubehör	Stromkabel, VGA Kable, Tasche, Fernbedienung, User Manual (CD)

©2011 Vivitek Corporation. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice. This product may be subject to export regulations. Vivitek is a trademark of Vivitek Corporation. Projection images are simulated.

